



POLYESTER SONSUZ BANT

Polyester Sonsuz Bant, Tek Kat, Emniyet Kat sayısı 7:1 (EN 1492-1)

								
Art No.	Renk kodu	Düz Kaldırma	U Kaldırma	Boğma	Açılı Kaldırmalar (0 - 45°)	(45°- 60°)	Genişlik (mm)	L1 min. (mm)
Kaldırma Kapasitesi (kg)								
L2542 10 01		1000	2000	800	1400	1000	30	500
L2542 10 02		1000	2000	800	1400	1000	50	500
L2542 20 01		2000	4000	1600	2800	2000	60	500
L2542 30 01		3000	6000	2400	4200	3000	90	600
L2542 40 01		4000	8000	3200	5600	4000	120	700
L2542 50 01		5000	10000	4000	7000	5000	150	800
L2542 60 01		6000	12000	4800	8400	6000	180	1000
L2542 80 01		8000	16000	6400	11200	8000	240	1000
L2542 11 01		10000	20000	8000	14000	10000	300	1000

* Talep üzerine farklı uzunluk, renk ve kapasitede üretim yapılabilir.

* Yukarıdaki kapasite tablosu simetrik yük kaldırmaları için geçerlidir.



L1 = kullanım uzunluğu
(L1 x 2 = çevre uzunluğu)