


POLYESTER GÖZLÜ SAPAN

Polyester Sapan, Çift Kat, Emniyet Katsayısı 7:1 (EN1492-1)

									
Art No.	Renk kodu	Düz Kaldırma	U Kaldırma	Boğma	Açılı Kaldırmalar (0 - 45°)	(45° - 60°)	Genişlik (mm)	L1 min. (mm)	L2 (mm)
Kaldırma Kapasitesi (kg)									
L2561 96 52		1000	2000	800	1400	1000	30	900	300
L2561 96 52		1000	2000	800	1400	1000	50	800	300
L2561 97 52		2000	4000	1600	2800	2000	60	900	300
L2561 97 82		3000	6000	2400	4200	3000	90	1000	350
L2561 98 52		4000	8000	3200	5600	4000	120	1400	500
L2562 00 02		5000	10000	4000	7000	5000	150	1500	550
L2562 01 02		6000	12000	4800	8400	6000	180	1700	650
L2562 02 02		8000	16000	6400	11200	8000	240	2100	800
L2562 03 02		10000	20000	8000	14000	10000	300	2500	1000



* Talep üzerine farklı uzunluk, renk ve kapasitede üretim yapılabilir.

* Yukarıdaki kapasite tablosu simetrik yük kaldırmaları için geçerlidir.